





SYMBOL: **4932478920**

MANUFACTURER: Milwaukee EAN: 4058546362027

4932478920 - BOLT™200 ventilated black safety helmet

- Shell made of Lexan™ ultra resistant to impacts.
- $\bullet \, \mathsf{BOLT}^{\scriptscriptstyle\mathsf{TM}} \, \, \mathsf{system-ensure} \, \, \mathsf{compatibility} \, \mathsf{among} \, \mathsf{a} \, \mathsf{large} \, \mathsf{range} \, \, \mathsf{of} \, \mathsf{accessories} \, \mathsf{with} \, \mathsf{an} \, \mathsf{easy} \, \mathsf{and} \, \mathsf{intuitive} \, \mathsf{attachment} \, \mathsf{accessories} \, \mathsf{mond} \, \mathsf{accessories} \, \mathsf{accessories} \, \mathsf{mond} \, \mathsf{accessories} \, \mathsf{a$
- Extremely comfortable and easy to adjust wheel ratchet adjustment system.
- Foam suspension provides consistent impact performance independent of impact location.



488,80 zt -10%

439,92 zł (tax excl.) (541,10 zł (tax incl.))



Product page link > https://imilwauke.pl/en/27004-4932478920-bolt200-ventilated-black-safety-helmet.html





DESCRIPTION

- · Comfortable inner foam suspension paired with a crown liner for extra comfort.
- Breathable, washable and replaceable premium sweatband.
- Breathable, washable and replaceable premium crown liner.
- · Vented version delivered with a mounted EN 12492 certified chinstrap (colour coded red).
- Unvented version delivered with a mounted EN 397 certified chinstrap (colour coded grey).
- Certified as per EN 397:2012 with optional requirement for Extreme temperatures 40°C (vented and unvented version), Lateral Deformation (vented and unvented version) and Electrical insulation 440 V a.c. (unvented version).
- Vented version certified as per EN 12492:2012. Unvented version provides protection in conformity of EN12492: 2012 except clause 4.1.4.
- 8 colours available with matte finish: white, yellow, orange, red, black, green, blue and high visibility yellow. Vented version compliance to clause 5.3 of EN 50365 Electrically insulating helmets for use on low voltage installations.
- Storage: The helmet should be transported in sufficiently robust packaging to prevent accidental damage to the shell or harness.
- Storage temperature range: $+5^{\circ}$ C $\sim +35^{\circ}$ C, <85% relative humidity, away from direct sunlight
- · Usage: Before and after each use, inspect the shell, suspension and lining for breakage, cracks, craze pattern, discoloration, chalky appearance, or any other unusual condition.
- If any of these conditions exist, replace the helmet immediately, as these conditions can indicate that the helmet has lost its capacity to protect from impact, penetration, and/or electrical shock · Weight: 545 g

FEATURES

Symbol	4932478920
Nazwa	hełm ochronny czarny wentylowany BOLT™200
Тур	hełm ochronny

