



SYMBOL: **4933479860** MANUFACTURER: **Milwaukee** EAN: **4058546376543**



M18 FPD3-502X - Percussion drill 158 Nm, 18 V, 5.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933479860

- Voltage: 18 V
- Max. torque: 158 Nm
- No load speed gear 1/2: 0-500/0-2100 rpm
- Max. drilling wood/steel/masonry: 89/16/16 mm
- Max. percussion rate: 0-33000 bpm
- Chuck capacity: 13 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Weight with battery pack (M18 B5): 2.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 749,00 zł~~ **-274,90 zł**

2 474,10 zł (tax excl.)

(3 043,14 zł (tax incl.))

PayU



Product page

link > <https://imilwauke.pl/en/27611-m18-fpd3-502x-percussion-drill-158-nm-18-v-50-ah-fuel-in-case-with-...>

DESCRIPTION

- Vibration screw driving: 1.48 m/s²
- Vibration drilling into concrete: 11.3 m/s²
- Vibration drilling into metal: 1.85 m/s²
- Sound pressure level (LPA): 95.78 dB(A)
- Sound power level (LWA): 106.78 dB(A)
- Higher power efficiency under load with outstanding torque of 158 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- AUTOSTOP™ control mode offers enhanced safety for the operator by preventing over-rotation in a bind-up.
- 13 mm metal chuck for quick bit changes and bit retention.
- Fastest drilling and driving applications under load.
- Brighter LED workspace illumination.
- Fuel gauge displays remaining charge.
- All metal reversible belt clip to hang your tool quickly and easily.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M18FPD3-502X
Typ	udarowa
Nm max	158.00
Częstość udaru [ud/min]	0-33000
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Średnica wiercenia w murze	16.00
Obroty [obr/min]	0-500/0-2100

