



SYMBOL: **4933479862** MANUFACTURER: **Milwaukee** EAN: **4058546376567**



M18 FDD3-0X - Drill driver 158 Nm, 18 V, FUEL™, in case, without equipment, 4933479862

- Voltage: 18 V
- Max. torque: 158 Nm
- No load speed gear 1/2: 0-500/0-2100 rpm
- Max. drilling wood/steel: 89/16 mm
- Chuck capacity: 13 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B5): 2.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



1 479,00 zł **-10%**

1 331,10 zł (tax excl.)

(1 637,25 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://imilwauke.pl/en/27612-m18-fdd3-0x-drill-driver-158-nm-18-v-fuel-in-case-without-equipment...>

DESCRIPTION

- Vibration screw driving: 1.48 m/s²
- Vibration drilling into metal: 1.85 m/s²
- Sound pressure level (LPA): 95.78 dB(A)
- Sound power level (LWA): 106.78 dB(A)
- Higher power efficiency under load with outstanding torque of 158 Nm.
- Extremely compact design of 173 mm length for access into tight spaces.
- AUTOSTOP™ control mode offers enhanced safety for the operator by preventing over-rotation in a bind-up.
- Fastest drilling and driving applications under load.
- Brighter LED workspace illumination.
- Fuel gauge displays remaining charge.
- All metal reversible belt clip to hang your tool quickly and easily.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18FDD3-0X
Typ	bezударowa
Nm max	158.00
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Obroty [obr/min]	0-500/0-2100