




SYMBOL: **4933492482** MANUFACTURER: **Milwaukee** EAN: **4058546418496**



## M18 BLHACD26-0X - Brushless 26 mm SDS-Plus D-Handle hammer 18 V, in case, without equipment, 4933492482

- Voltage: 18 V
- Blow energy: 2.6 J
- Max. percussion rate: 0-4600 bpm
- No load speed: 0-1270 rpm
- Max. drilling concrete/wood/steel: 26/28/13 mm
- Tool reception: SDS-Plus
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B4): 3.1 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~1 289,00 zł~~ **-10%**

**1 160,10 zł** (tax excl.)

(1 426,92 zł (tax incl.))

PayU  

Product page

link > <https://imilwauke.pl/en/27681-m18-blhacd26-0x-brushless-26-mm-sds-plus-d-handle-hammer-18-v-in-ca...>

### DESCRIPTION

- Vibration drilling: 13.9 m/s<sup>2</sup>
- Vibration chiseling: 13.2 m/s<sup>2</sup>
- Sound pressure level (LPA): 93.5 dB(A)
- Sound power level (LWA): 104.5 dB(A)
- D-handle with lightweight and ergonomic design for increased end user comfort.
- Powerful hammer mechanism and the brushless motor design delivers 2.6 J of impact energy.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Anti-vibration system (AVS) for decreased user fatigue and lower vibration exposure.
- All metal gear case, optimum seating of the gears for enhanced service life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Brushless motor, REDLITHIUM™ battery pack and REDLINK™ electronic deliver power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) without battery and charger.**

### FEATURES

|                              |                |
|------------------------------|----------------|
| Symbol                       | M18BLHACD26-0X |
| Waga [kg]                    | 3.10           |
| Uchwyt                       | SDS-Plus       |
| Częstość uderu [ud/min]      | 0-4600         |
| Energia uderu                | 2.60           |
| Ilość akumulatorów           | brak           |
| Zasilanie                    | battery        |
| Napięcie akumulatora [V]     | 18             |
| Średnica wiercenia w betonie | 26.00          |
| Średnica wiercenia w drewnie | 28.00          |
| Średnica wiercenia w metalu  | 13.00          |
| Obrotu [obr/min]             | 0-1270         |