



SYMBOL: **4933492802** MANUFACTURER: **Milwaukee** EAN: **4058546476731**



M18 ONEDD3-502X - Drill driver 158 Nm, 18 V, 5.0 Ah, ONE-KEY™, in case, with 2 batteries and charger, 4933492802

- Voltage: 18 V
- Max. torque: 158 Nm
- No load speed gear 1/2: 0-500/0-2100 rpm
- Max. drilling wood/steel: 89/16 mm
- Chuck capacity: 13 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Weight with battery pack (M18 B5): 2.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 629,00 zł~~ **-10%**

2 366,10 zł (tax excl.)

(2 910,30 zł (tax incl.))

PayU



Product page

link > <https://imilwauke.pl/en/30981-m18-onedd3-502x-drill-driver-158-nm-18-v-50-ah-one-key-in-case-with...>

DESCRIPTION

- Vibration screw driving: 1.48 m/s²
- Vibration drilling into metal: 1.85 m/s²
- Sound pressure level (LPA): 95.78 dB(A)
- Sound power level (LWA): 106.78 dB(A)
- Higher power efficiency under load - outstanding torque of 158 Nm.
- Extremely compact design of 173 mm length for access into tight spaces.
- Connect via Bluetooth® with the ONE-KEY™ app.
- Save up to 3 custom settings to the tools memory for fast selection on the jobsite.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality.
- Adjustable trigger control for all applications with ONE-KEY™.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Control speed, torque, start and end speeds, anti-kickback functions and LED.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard Equipment: Belt clip, side handle.
- **Supplied in case (HD Box) with 2 batteries and charger.**

FEATURES

Symbol	M18ONEDD3-502X
Typ	bezударowa
Nm max	158.00
Ilość akumulatorów	2
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	89.00
Średnica wiercenia w metalu	16.00
Obroty [obr/min]	0-500/0-2100

