





SYMBOL: 4933493304

MANUFACTURER: Milwaukee EAN: 4058546481759

\*\*\*\*

## M18 FR12-0X - Router 12 mm, 18 V, FUEL™, in case, without equipment

- · Voltage: 18 V
- Collect capacity: 12.7 mm
- Plunge capacity: 60 mm
- Speed settings: 6
- No load speed: 12000-25000 rpm
- · Battery type: Li-ion
- No. of batteries supplied: 0
- Weigth with battery pack (M18 HB5.5): 4 kg

**■** WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)





2 069,10 zł (tax excl.)

(2 544,99 zł (tax incl.))



PayU' VISA MasterCard













Product page link > https://imilwauke.pl/en/30990-m18-fr12-0x-router-12-mm-18-v-fuel-in-case-without-equipment.html

## DESCRIPTION

- POWERSTATE™ brushless motor in combination with the HIGH OUTPUT™ 5.5 Ah battery pack supplies constant power for faster
- cuts and reduced heat in high demand applications with the equivalent amount of power as a corded unit.

  Variable speed from 12,000 RPM to 25,000 RPM for clean and accurate cutting in a wide range of material.
- Fast and accurate micro depth adjustments with no slop, secure macro adjustments, and clear line of sight to the bit when routing the workpiece.
- Unobstructed line of sight to the bit to gauge cut quality, feed rate, and material removed per pass.
- Easily controlled with one hand, comfortable to use at extended duration's, and well-balanced across the base plate onto the work surface.
- Guide rail compatible, gives the user a secure and efficient method to attach their router bases to a guide rail system to cut straight lines on any work surface.
   Collet diameters are 12 mm, 1/2\*, 8 mm, 1/4\*.

- DEK 26 quick dust extraction connector makes the router compatible with any MILWAUKEE® vac.
- The DNA of our FUEL" platform redefines the balance of cordless technologies. MILWAUKEE'S' POWERSTATE" brushless motor, REDLITHIUM" battery pack and REDLINK PLUS" electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries
- Standard Equipment: 1/4", 8 mm. 12 mm. 1/2" collets, side fence, sub-base, wrench, dust extraction pipe.
- · Supplied in case (HD Box) without battery and charger.

LATORES	
Symbol	M18FR12-0X
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	12000-25000

