



SYMBOL: **4933480756** MANUFACTURER: **Milwaukee** EAN: **4058546410414**



M12 FPTR-0 - Pass-through ratchet 12 V, FUEL™, INSIDER™, without equipment

- Voltage: 12 V
- Max. torque: 81 Nm
- No load speed: 0-350 rpm
- Head profile: 21.45 mm
- Length: 386 mm
- Tool reception: 14.4 mm Hex
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M12 B2): 1.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 429,00 zł~~ **-10%**

1 286,10 zł (tax excl.)

(1 581,90 zł (tax incl.))

PayU **VISA** **MasterCard**

Product page

link > <https://imilwauke.pl/en/31857-m12-fptr-0-pass-through-ratchet-12-v-fuel-insider-without-equipment...>

DESCRIPTION

- With up to 81 Nm of max torque and 350 rpm's, this tool offers the perfect combination of power and speed.
- Features the lowest-profile head for best-in-class access in confined spaces.
- The extended neck allows users better access in hard-to-reach places.
- Pass-through sockets up to a size of 15 mm allow users to comfortably fasten and unfasten nuts on bolts of any length.
- The included 1/4" and 3/8" anvil adapters and 1/4" Hex bit holder makes it the most versatile ratcheting solution.
- Variable speed metal trigger provides ultimate control of the tool.
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use.
- The dual LED lights illuminate the work area while the on-board fuel gauge displays remaining run time.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Standard Equipment: pass-through sockets from 8 mm to 15 mm, sockets without pass-through functionality from 16 mm to 19 mm as well as 21 mm, 1/4" and 3/8" anvil adapter, 1/4" Hex bit holder.
- **Supplied without battery and charger.**

FEATURES

Symbol	M12FPTR-0
Wyjście	1/4"
Nm max	81
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-350