





SYMBOL: **4933499413**

MANUFACTURER: Milwaukee EAN: 4058546565770

M12 FPTR-0 - Pass-through ratchet 12 V, FUEL™, INSIDER™, without equipment, 4933499413

- Voltage: 12 V
- Max. torque: 81 Nm
- No load speed: 0-350 rpm
- Head profile: 21.45 mm
- · Length: 386 mm
- Tool reception: 14.4 mm Hex
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M12 B2): 1.2 kg



1 339,00 zł -10%

1 205,10 zł (tax excl.)

(1 482,27 zł (tax incl.))

















link > https://imilwauke.pl/en/31857-m12-fptr-0-pass-through-ratchet-12-v-fuel-insider-without-equipment...

DESCRIPTION

- With up to 81 Nm of max torque and 350 rpm's this tool offers the perfect combination of power and speed
- Features the lowest-profile head for best-in-class access in confined spaces.
- The extended neck allows users better access in hard-to-reach places.
 Pass-through sockets up to a size of 15 mm allow users to comfortably fasten and unfasten nuts on bolts of any length.
- The included 1/4° and 3/8° anvil adapters and 1/4° Hex bit holder makes it the most versatile ratcheting solution.
 Variable speed metal trigger provides ultimate control of the tool.
- Premium rubber overmold withstands corrosive materials and provides increased comfort when in use
- The dual LED lights illuminate the work area while the on-board fuel gauge displays remaining run time.
 The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor,
- REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
 Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Standard Equipment: pass-through sockets from 8 mm to 15 mm, sockets without pass-through functionality from 16 mm to 19 mm as well as 21 mm, 1/4* and 3/8* anvil adapter, 1/4* Hex bit holder.
- · Supplied without battery and charger.

FEATURES

Symbol	M12FPTR-0
Wyjście	1/4"
Nm max	81
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-350

