



SYMBOL: **4933493553** MANUFACTURER: **Milwaukee** EAN: **4058546484248**



M18 FSAGSVO125X-502X - Safety grinder with variable speed 125mm 18V, 5.0Ah ONE-KEY™, paddle switch, with 2 batteries, 4933493553

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- Bore size: 14 mm
- No load speed: 3500-8500 rpm
- Switch type: Deadman switch
- Brake: yes
- Braking time: < 1 s
- Line lock out function: yes
- Variable speed: yes
- Regulacja prędkości: yes
- Anti-kickback protection: yes
- AVS anti-vibration system: yes

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~3 489,00 zł~~ **-10%**

3 140,10 zł (tax excl.)
(3 862,32 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/32499-m18-fsagsvo125x-502x-safety-grinder-with-variable-speed-125mm-18v-5...>

DESCRIPTION

- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Weight with battery pack (M18 B5): 3 kg
- Dual trigger activation requires the user to have always both hands on the tool and automatically shuts down the tool whenever one hand is taken off.
- RAPIDSTOP™ for fastest disc brake in less than 1 second and best user protection.
- AUTOSTOP™ shuts down the tool to protect the user in bind-up situations or any unnatural movement
- Delivering corded performance similar to a 1200 W grinder.
- Maximum control for every application with 4-mode push button, ideal for working with stainless steel and aluminium & for rust and paint removal.
- Lowest vibration in its class – 3.27 m/s² for surface grinding.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality.
- Multi-position & non-removable side handle, allowing the user to tilt and rotate the handle into 15 different positions for ideal handling & easy storage.
- Non-removal guard, guard adjustment and cutting guard clip installation is tool-free.
- Integrated FIXTEC™ system for tool-free wheel change.
- Non-lockable safety paddle switch on the main handle and non-lockable trigger on the side handle.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard Equipment: Quick release safety guard, cutting guard clip, flange, flange nut, spanner
- **Supplied In case (HD Box) with 2 batteries and charger.**

FEATURES

Symbol	M18FSAGSVO125X-502X
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica tarczy	125.00
Typ włącznika	łopatkowy
Obroty [obr/min]	3500-8500